



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

**Material Safety Data Sheet (MSDS)**

1. Identification of the Product and Supplier					
<b>Product:</b>					
<b>LITHIUM-ION RECHARGEABLE BATTERY</b>					
<b>Trade name and model:</b>			<b>LITHIUM-ION RECHARGEABLE BATTERY</b>		
<b>Model:</b>			<b>ELI-2800E</b>		
<b>Cells model:</b>			<b>VL34570-GEN5</b>		
<b>Battery Wh:</b>			<b>39 Wh (2 cells)</b>		
<b>Supplier:</b>					
<b>EPSILOR ELECTRONIC INDUSTRIES LTD</b> Temed Science Park M.P. Arava 86800, ISRAEL <b>Phone: +972-8-6556280</b> Fax: +972-8-6555960					
2. Composition & Information on Ingredients					
Component		Material		Formula	
Positive Electrode		Lithium Cobalt Oxide		LiCoO <sub>2</sub>	
Negative Electrode		Carbon		C	
Electrolyte		Solution of lithium hexafluorophosphate In a mixture of organic solvents** **Ethylene Carbonate - Solvent DiMethyl Carbonate - Solvent		LiPF <sub>6</sub>	
<b><u>COMPOSITION</u> (typical weight percentages of basic material)</b>					
Metals	%	Plastics	%	Others	%
Steel, Copper, Aluminum	31	polypropylene	10	- Lithium cobaltite - Carbon - Organic solvents - Salrs - Lithium metal	29 16 13 1 0
3. Hazards Identification					
The rechargeable Lithium-Ion batteries described in this Material Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the manufacturer and as long as their integrity is maintained.					
Do not short circuit, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion.					



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

Under normal conditions of use, the electrode materials and electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.

ELI-2800E batteries are fitted with a safety vent for protection incase of excessive internal pressure and/or temperature

#### **4. First Aid Measures**

In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out fumes/gases.

If it occurs, by accident, seek medical attention and the following measures must be taken:

<b>Inhalation</b>	Not anticipated under normal use. Remove from exposure, Remove to fresh air, rest and keep warm. In severe cases obtain medical attention.
<b>Skin Contact</b>	Not anticipated under normal use. Wash off skin thoroughly with water. Remove contaminated clothing and wash before reuse. In severe cases obtain medical attention.
<b>Eye Contact</b>	Not anticipated under normal use. Irrigate thoroughly with water for at least 15 minutes. Obtain medical attention.
<b>Ingestion</b>	Not anticipated under normal use. Wash out mouth thoroughly with water and give plenty of water to drink.
<b>Further Treatment</b>	All cases of eye contamination, persistent skin irritation and casualties who have swallowed this substance or been affected by breathing its vapors should be seen by a doctor.

#### **5. Fire Fighting Measures**

Dry chemical type or CO<sub>2</sub> extinguishers, Halon, or copious quantities of water or water-based foam can be used to

cool down burning Li-ion cells and batteries. During water application, caution should be exercised as burning pieces of flammable particles may be ejected from the fire.


Do not re-enter the area until it has been adequately purged of the fire vapour and extinguishing agent.

In case of fire, it is recommended to wear self-contained breathing apparatus, to avoid contact with irritant fumes. Evacuate all persons from immediate area of fire.

<b>Extinguishing Media</b>	Use CO <sub>2</sub> extinguishers or copious quantities of water or water-based foam <b>Do not use type D extinguishers</b>
----------------------------	--






**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

<b>6. Accidental Release Measures</b>	
<p>In case of electrolyte leakage from a cell or battery, do not inhale the gas as possible. Remove personnel from area.</p> <p>If the skin has come into contact with the electrolyte it should be washed thoroughly with water.</p> <p>Using protective glasses and gloves, sand or earth should be used to absorb any exuded material.</p> <p>Seal leaking battery and contaminated absorbent material in plastic bag and dispose of as Special Waste in accordance with local regulations.</p>	
<b>7. Handling and Storage</b>	
<b>Handling</b>	<p>Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e. metal) goods. Do not directly heat or solder. Do not throw into fire.</p> <p>Do not mix batteries of different types and brands. Do not mix new and used batteries. Keep batteries in non conductive (i.e. plastic) trays.</p> <p>Do not disassemble, mutilate or mechanically abuse cells and batteries.</p>
<b>Storage</b>	<p>Store in a cool (preferably below 30°C) and ventilated area, away from moisture, sources of heat, open flames, food and drink. Keep adequate clearance between walls and batteries. Temperature above 70°C may result in battery leakage and rupture. Since short circuit can cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do not jumble them.</p>
<b>Other</b>	<p>Follow Manufacturer's recommendations regarding maximum recommended currents and operating temperature range. Applying pressure on deforming the battery may lead to disassembly followed by eye, skin and throat irritation. Do not immerse in water. Connecting to inappropriate power supplies can result in fire or explosion.</p>
<b>8. Exposure Controls &amp; Personal Protection</b>	
<b>Occupational exposure standard</b>	See section 2
	<p style="text-align: center;"><b>Respiratory protection</b></p> <p>In all fire situations, use self-contained breathing apparatus.</p>



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

	<b>Hand protection</b>	In the event of leakage wear gloves.
	<b>Eye protection</b>	Safety glasses are recommended In case of leaking or rupture cells.
	<b>Other</b>	In the event of leakage wear chemical apron.

**9. Physical and Chemical Properties**

<b>Appearance</b>	Small prismatic cylindrical shape hermetically sealed and fitted with an external plastic sleeving.
<b>Odor</b>	Odourless
<b>pH</b>	Not applicable
<b>Flash Point</b>	Not applicable
<b>Flammability</b>	Not applicable
<b>Relative Density</b>	> 2% g/cm <sup>3</sup>
<b>Solubility (water)</b>	Not applicable (unless inner components exposed)
<b>Solubility (other)</b>	Not applicable

**10. Stability and Reactivity**

Product is stable under conditions described in Section 7.

<b>Conditions to avoid</b>	Heat above 70°C or incinerate. Deform. Mutilate. Crush. Pierce. Disassemble. Short circuit. Expose over a long period to humid conditions.
<b>Materials to avoid</b>	NA
<b>Hazardous decomposition products</b>	HF, CO, CO <sub>2</sub>

**11. Toxicological Information**

<b>Signs &amp; symptoms</b>	None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibriotic lung injury and membrane irritation.
<b>Inhalation</b>	Lung irritant.
<b>Skin contact</b>	Skin irritant



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

<b>Eye contact</b>	Eye irritant.
<b>Ingestion</b>	Tissue damage to throat and gastro/respiratory tract if swallowed.
<b>Medical conditions generally aggravated by exposure</b>	In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.

**12. Ecological Information**

<b>Mammalian effects</b>	None known if used/disposed of correctly.
<b>Eco-toxicity</b>	None known if used/disposed of correctly.
<b>Bioaccumulation potential</b>	None known if used/disposed of correctly.
<b>Environmental fate</b>	None known if used/disposed of correctly.

**13. Disposal Considerations**

Do not incinerate, or subject cells to temperatures in excess of 70oC. Such abuse can result in loss of seal, leakage, and/or cell explosion.  
 The Lithium Ion batteries are classified as non-hazardous waste and are safe for disposal in the normal municipal waste stream. Dispose of in accordance with appropriate local regulations.

**14. Transport Information**

<b>Label for conveyance</b>	
<b>UN Number</b>	UN3480
<b>Shipping Name</b>	Lithium Ion Battery
<b>Hazard Classification</b>	The battery is not considered to be under hazardous classification.
<b>Packing Instruction</b>	IATA, PI 965 section II.
<b>Documentation</b>	Each consignment must be accompanied with document containing information required for UN 3480 Excepted

**15. Regulatory Information**

Regulations specifically applicable:  
 -ACGIH and OSHA  
 -IATA/ICAO (air transportation) UN 3480 or UN 3481  
 -IMDG (sea transportation) : UN 3480 or UN 3481  
 -Transportation within the US-DOT, 49 Code of Federal Regulations



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

**16. Other Information**

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

Epsilon does not accept liability for any loss damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. Epsilon does not offer warranty against patent infringement. Additional information is available by calling the telephone number above.