



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

**Material Safety Data Sheet (MSDS)**

1. Identification of the Product and Supplier		
<b>Product:</b>		
<b>LITHIUM-ION RECHARGEABLE BATTERY</b>		
<b>Trade name and model:</b>	<b>LITHIUM-ION RECHARGEABLE BATTERY</b>	
<b>Model:</b>	<b>MR-2791</b>	
<b>Cells model:</b>	<b>ICR18650-26C (24 cells)</b>	
<b>Battery Wh:</b>	<b>216 Wh</b>	
<b>Supplier:</b>		
<b>EPSILOR ELECTRONIC INDUSTRIES LTD</b> Temed Science Park M.P. Arava 86800, ISRAEL <b>Phone: +972-8-6556280</b> Fax: +972-8-6555960		
2. Composition & Information on Ingredients		
INGREDIENTS	%	CAS NUMBER
Aluminum Foil	2-10	7429-90-5
Metal Oxide (proprietary)	20-50	Confidential
Polyvinylidene Fluoride (PVDF)	<5	24937-79-9
Styrene Butadiene Rubber(SBR)	<5	9003-55-8
Copper Foil	2-10	7440-50-8
Carbon (proprietary)	10-30	7440-44-0
Electrolyte (proprietary)	10-20	Confidential
Aluminum and inert materials	Remainder	N/A
3. Hazards Identification		
<p>The rechargeable Lithium-Ion batteries described in this Material Safety Data Sheet are sealed units which are not hazardous when used according to the recommendations of the manufacturer and as long as their integrity is maintained.</p> <p>Do not short circuit, recharge, puncture, incinerate, crush, immerse, force discharge or expose to temperatures above the declared operating temperature range of the product. Risk of fire or explosion.</p> <p>Under normal conditions of use, the electrode materials and electrolyte they contain are not exposed to the outside, provided the battery integrity is maintained and seals remain intact. Risk of exposure only in case of abuse (mechanical, thermal, electrical) which leads to the activation of safety valves and/or the rupture of the battery containers. Electrolyte leakage, electrode materials reaction with moisture/water or battery vent/explosion/fire may follow, depending upon the circumstances.</p>		







**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

<b>4. First Aid Measures</b>	
In case of battery rupture or explosion, evacuate personnel from contaminated area and provide maximum ventilation to clear out fumes/gases. If it occurs, by accident, seek medical attention and the following measures must be taken:	
<b>Inhalation</b>	Not anticipated under normal use. Remove from exposure, Remove to fresh air, rest and keep warm. In severe cases obtain medical attention.
<b>Skin Contact</b>	Not anticipated under normal use. Wash off skin thoroughly with water. Remove contaminated clothing and wash before reuse. In severe cases obtain medical attention.
<b>Eye Contact</b>	Not anticipated under normal use. Irrigate thoroughly with water for at least 15 minutes. Obtain medical attention.
<b>Ingestion</b>	Not anticipated under normal use. Wash out mouth thoroughly with water and give plenty of water to drink.
<b>Further Treatment</b>	All cases of eye contamination, persistent skin irritation and casualties who have swallowed this substance or been affected by breathing its vapors should be seen by a doctor.
<b>5. Fire Fighting Measures</b>	
CO <sub>2</sub> extinguishers or copious quantities of water or water-based foam can be used to cool down burning Li-Ion cells and batteries. During water application, caution should be exercised as burning pieces of the flammable particle may be ejected from the fire.  In case of fire, it is recommended to wear self-contained breathing apparatus, to avoid contact with irritant fumes. Evacuate all persons from immediate area of fire.	
<b>Extinguishing Media</b>	Use CO <sub>2</sub> extinguishers or copious quantities of water or water-based foam <b>Do not use type D extinguishers</b>
<b>6. Accidental Release Measures</b>	
In case of electrolyte leakage from a cell or battery, do not inhale the gas as possible. Remove personnel from area.  If the skin has come into contact with the electrolyte it should be washed thoroughly with water.  Using protective glasses and gloves, sand or earth should be used to absorb any exuded material.  Seal leaking battery and contaminated absorbent material in plastic bag and dispose of as Special Waste in accordance with local regulations.	



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

7. Handling and Storage	
<b>Handling</b>	<p>Do not crush, pierce, short (+) and (-) battery terminals with conductive (i.e. metal) goods. Do not directly heat or solder. Do not throw into fire.</p> <p>Do not mix batteries of different types and brands. Do not mix new and used batteries. Keep batteries in non conductive (i.e. plastic) trays.</p> <p>Do not disassemble, mutilate or mechanically abuse cells and batteries.</p>
<b>Storage</b>	<p>Store in a cool (preferably below 30°C) and ventilated area, away from moisture, sources of heat, open flames, food and drink. Keep adequate clearance between walls and batteries. Temperature above 70°C may result in battery leakage and rupture. Since short circuit can cause burn, leakage and rupture hazard, keep batteries in original packaging until use and do not jumble them.</p>
<b>Other</b>	<p>Follow Manufacturer's recommendations regarding maximum recommended currents and operating temperature range. Applying pressure on deforming the battery may lead to disassembly followed by eye, skin and throat irritation. Do not immerse in water.</p> <p>Connecting to inappropriate power supplies can result in fire or explosion.</p>

8. Exposure Controls & Personal Protection		
<b>Occupational exposure standard</b>		See section 2
	<b>Respiratory protection</b>	In all fire situations, use self-contained breathing apparatus.
	<b>Hand protection</b>	In the event of leakage wear gloves.
	<b>Eye protection</b>	Safety glasses are recommended In case of leaking or rupture cells.
	<b>Other</b>	In the event of leakage wear chemical apron.



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

<b>9. Physical and Chemical Properties</b>	
<b>Appearance</b>	Small prismatic cylindrical shape, hermetically sealed and fitted with an external plastic sleeving.
<b>Odor</b>	Odourless
<b>pH</b>	Not applicable
<b>Flash Point</b>	Not applicable
<b>Flammability</b>	Not applicable
<b>Relative Density</b>	> 2% g/cm <sup>3</sup>
<b>Solubility (water)</b>	Not applicable (unless inner components exposed)
<b>Solubility (other)</b>	Not applicable
<b>10. Stability and Reactivity</b>	
Product is stable under conditions described in Section 7.	
<b>Conditions to avoid</b>	Heat above 70°C or incinerate. Deform. Mutilate. Crush. Pierce. Disassemble. Short circuit. Expose over a long period to humid conditions.
<b>Materials to avoid</b>	NA
<b>Hazardous decomposition products</b>	HF, CO, CO <sub>2</sub>
<b>11. Toxicological Information</b>	
<b>Signs &amp; symptoms</b>	None, unless battery ruptures. In the event of exposure to internal contents, corrosive fumes will be very irritating to skin, eyes and mucous membranes. Overexposure can cause symptoms of non-fibriotic lung injury and membrane irritation.
<b>Inhalation</b>	Lung irritant.
<b>Skin contact</b>	Skin irritant
<b>Eye contact</b>	Eye irritant.
<b>Ingestion</b>	Tissue damage to throat and gastro/respiratory tract if swallowed.
<b>Medical conditions generally aggravated by exposure</b>	In the event of exposure to internal contents, eczema, skin allergies, lung injuries, asthma and other respiratory disorders may occur.
<b>12. Ecological Information</b>	
<b>Mammalian effects</b>	None known if used/disposed of correctly.
<b>Eco-toxicity</b>	None known if used/disposed of correctly.
<b>Bioaccumulation potential</b>	None known if used/disposed of correctly.
<b>Environmental fate</b>	None known if used/disposed of correctly.



**EPSILOR**  
**ELECTRONIC INDUSTRIES LTD**

**13. Disposal Considerations**

Do not incinerate, or subject cells to temperatures in excess of 70°C. Such abuse can result in loss of seal, leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations

**14. Transport Information**

<b>Label for conveyance</b>	Class 9 Label
<b>UN Number</b>	UN3480
<b>Shipping Name</b>	Lithium Ion Batteries
<b>Hazard Classification</b>	Class 9
<b>Packing Instruction</b>	IATA , PI 965 section I.
<b>Documentation</b>	Each consignment must be accompanied with DGD document.

**15. Regulatory Information**

Regulations specifically applicable:

- ACGIH and OSHA: see exposure limits of internal ingredients of the battery in section 8
- IATA/ICAO (air transportation) UN 3480 or UN 3481
- IMDG (sea transportation) : UN 3480 or UN 3481
- Transportation within the US-DOT, 49 Code of Federal Regulations

**16. Other Information**

This information has been compiled from sources considered to be dependable and is, to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty (either expressed or implied) or guarantee is made to the accuracy, reliability or completeness of the information contained herein.

This information relates to the specific materials designated and may not be valid for such material used in combination with any other materials or in any process. It is the user's responsibility to satisfy himself as to the suitability and completeness of this information for his particular use.

Epsilon does not accept liability for any loss damage that may occur, whether direct, indirect, incidental or consequential, from the use of this information. Epsilon does not offer warranty against patent infringement. Additional information is available by calling the telephone number above.